# BenQ Education

# RP7503

**Pro Series** 















# **ClassroomCare®** - Unique health protection technology



BenQ displays feature the world's first germ-resistant touchscreen for large format displays, with official TÜV and SIAA certification. RP03 interactive displays employ Nano-ionic silver particles on the screen, front ports, pens, and remote control to protect students and teachers across all points of contact



**Air Quality Sensor** to detect & monitor the level of carbon dioxide (CO<sub>2</sub>), formaldehyde (CH<sub>2</sub>O), volatile organic compounds (TVOCs) concentration and presence of PM<sub>25</sub> and PM<sub>10</sub> (air pollution) in the classroom. Built-in **Air Ionizer** to reduce particle pollution in the classroom, the widget can actively release negative ions automatically or remotely via DMS.



BenQ displays are equipped with anti-glare, flicker-free and low blue light eye-care features.
Embedded sensors activate the Smart Eye-care solution when anyone approaches the screen by turning on the low blue light mode automatically. RP03 is the World's first Eyesafe® certified interactive display.

	Screen size		75"
Panel	Resolution		4K UHD 3840 × 2160
	Brightness (typ.)		400 nits
	Contrast ratio (typ.)		1200 : 1
	Dynamic contrast ratio		30,000 : 1
	Viewing angle (H/V)		178°
	Response time (G-t-G)		8 ms
	Backlight life (hrs)		50,000
	Panel surface		AG, Haze 25%
	Operating hours		18 hours / 7 days
	Orientation		Landscape
Platform solution	System memory		8 GB
	Storage		64 GB
	os		Android 11
Power	Power supply		100-240 V 50/60 Hz
		Maximum (W/h)	461
	Power consumption	Typical (W/h)	90
		Standby mode (W/h)	<0.5
	AC power switch		Yes
	Wake up		LAN / HDMI / VGA / DP
Touch	Technology		Fine IR Plus
	Number of touch points		40
	Interface		USB Type B x 3
Glass	Tempered glass		3.2 mm
	Hardness		9H
	AG coating		Yes
ClassroomCare® Technology	Eye-Care Solution (TÜV certified) Flicker-Free & Low Blue Light		Smart Eye-Care (Eyesafe® certified)
	Air-Quality Sensor		CO <sub>2</sub> - PM <sub>2.5</sub> - PM <sub>10</sub> , Temperature & Humidity, Air Ionizer
	Germ-Resistant Screen (TÜV & SIAA certified)		Yes
Environment	Operation temperature		0°C ~ 40°C
	Operating humidity		20% ~ 80% RH non-condensing
	Energy efficiency		Energy Star 8.0 certified
Connectivity	Input		VGA x 1, HDMI 2.0 x 3, DP 1.2a x 1, Audio (3.5 mm) x 1
	Output		HDMI 2.0 x 1, Audio (3.5 mm) x 1
	USB		Type A x 7 (2.0 x 2 / 3.2 Gen 1 x 5), Type B x 3 (3.0), Type C x 2 (3.0)
	RS232		x 1
	RJ45 (LAN)		x 2 (Android / OPS) up to 1000Mbps
	Remote controller		x 1
Audio	Built-in speaker		2 x 16 W / 1 x Subwoofer 16 W
	Dolby Audio		Yes
	Array microphones		x 8
Mechanical	Dimension (mm)	Screen	1717.1 × 1065.3 × 121.3 mm
	Weight (kg)	Net weight	55.5
	5 ( 5)	Gross weight	70
	Bezel width (mm)		16.6 / 16.6 / 16.6 / 16.6
	Wall mounting (VESA) (screw type / max. length)		800 × 400 (4 × M8 × 25L)
	Wall mount kit		Included
	OPS slot		Yes
	NFC sensor		Yes
	Pen tray		Yes
Warranty			3-year warranty on-site exchange



## **EZWrite 6**



## InstaShare 2



## X-Sign Broadcast

Announcement system with cross-campus communication. Send visual alerts, warnings, videos to all or one specific device.





















NFC SENSOR & KEYPAD BUTTONS





CAMERA USB PORT, WIFI DONGLE & REMOTE CONTROLLER USB PORT





DOWN I/O



















SIDE I/O





















## **Benq**

